

## Access Software



One (1) to Unlimited Card Readers and Cardholders

- LINC-NXG ..... Access Control Software
- NXG-Photo ID ..... Photo ID Option
- NXG-EASY Lobby ..... Visitor Management Option
- NXG-View ..... CCTV and Graphics Option
- NXG-SMARTELV ..... Smart Elevator Interface Option (software interface) Ottis and Thyssenkrupp

For more info:  
[sales@1pcsc.com](mailto:sales@1pcsc.com)



## Access Controllers



All PCSC controllers are backward & forward compatible w/Access Control Software

### Fault Tolerant Series:

Providing 99% Availability for Alarm & Card Authorization, Peer-to-Peer, Automatic Communication Cutover

- FT ..... Fault Tolerant Controller
- DDM ..... Dual Door Module
- SDM ..... Single Door Module

*\*Other configurations available, Rack Mount, Network Display Screens, etc.*

### IQ Series:

Reader Priority Distributed Intelligence from 2 to 12 reader configurations, below configurations include: Controller, Enclosure, Power Supply & Ethernet Communications.

- IQ200 M PS LAN ..... 2 Reader capacity
- IQ400 M PS LAN ..... 4 Reader capacity
- IQ600 M PS LAN ..... 6 Reader capacity
- IQ800 M PS LAN ..... 8 Reader capacity
- IQ1000 M PS LAN ..... 10 Reader capacity
- IQ1200 M PS LAN ..... 12 Reader capacity

*\*Other configurations available, e.g., Alarm Inputs, Outputs - Contact PCSC*

### SIM Series:

Input Priority Distributed Intelligence Controllers 32 Supervised inputs - below configurations include: Controller, Enclosure, Power Supply & RS485 Communications.

- SIM L PS ..... 32 Supervised inputs - No reader Support
- SIM 400 L PS ..... 32 Supervised inputs - 4 reader Support
- SIM 800 L PS ..... 32 Supervised inputs - 8 reader Support

*\*Other configurations available, e.g., Alarm Inputs, Outputs & Ethernet Communications - Contact PCSC*

### Elevator Controllers:

- IQ2ELV ..... 2 cab interface, Up to 16 Relay Floors total
- IQ2ELV2 ..... 2 cab interface, Up to 32 Relay Floors total
- IQ2ELV3 ..... 2 cab interface, Up to 48 Relay Floors total
- IQ2ELV4 ..... 2 cab interface, Up to 64 Relay Floors total
- IQ4ELV ..... 4 cab interface, Up to 16 Relay Floors total
- IQ4ELV2 ..... 4 cab interface, Up to 32 Relay Floors total
- IQ4ELV3 ..... 4 cab interface, Up to 48 Relay Floors total
- IQ4ELV4 ..... 4 cab interface, Up to 64 Relay Floors total

*\*Other configurations available - Contact PCSC*

## Security Readers



### WaveLynx:

Available in Mullion, Wall switch and Free Mobile Credential-Compatible with HID 25KHz Proximity Technology/13.56 MHz - Open Standards

- ET-10-7WS ..... Mullion Reader - Dual Tech w/Mobile
- ET-20-7WS ..... Wall Switch Reader - Dual Tech w/Mobile
- ET-25-7WS ..... Reader/Keypad - Dual Tech w/Mobile

*\*Other configuration options available - Contact PCSC*

### Biometric Readers:

- SAFR Scan ..... Facial Recognition Multiple face detection up to 15 feet, On-Premise or Cloud with optional: Tailgating, Video Analytics